



Specifications:  
 Voltage Rating : 250V AC/DC  
 Withstand Voltage : 1500V AC/minute  
 Contact Resistance : 10mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(Min.)  
 Suitable for 0.64mm PIN  
 The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements



Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
33001T2P-2E-S-F	AWG #16~#18	2.10mm(max)	Copper alloy	Ni 50u" Min., Tin-plated 80u" Min.	8KPCS
33001T2P-3E-2-S-F	AWG #16~#18	2.10mm(max)	Copper alloy	Ni 50u" Min., Matte Tin-plated 80u" Min.	8KPCS

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART. NO.:	DWG. NO.:
A0	新图面发行	19.04.28	LINEAR	1:1			33001T2P-XX-S-F	ENDE05
A1	TN2006170123	20.06.15	0.0±0.25	APPROVED	张振坤	20.06.15		
			X° REF±6°	DESIGNER	张振坤	20.06.15	TITLE:	
			X° ±3°	DRAWN	张振坤	20.06.15	Molex 3.0 松端母端子	
			X° X'±2°					

**JCTC**®  
 TERMINAL&CONNECTORS  
 REV: A1 SHEET: 1/1